# Tri-color/anchor, silver w/FB base

**101-009-FB**

Horizontally mounted with 0,7m cable
FB (flat base) POM mounting system

| Specifications | |
|---|---|
| **Number** | 101-009-FB |
| **Dimensions metric** | Ø92,5mm x 36mm |
| **Certification** | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support |
| **Dimensions imperial** | Ø3.6" x 1.4" |
| **Approved to** | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| **Included In Package** | 1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide |
| **Operating temperature** | -25°C to 55°C |
| **Mounting** | Horizontal |
| **Materials** | Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| **Operating Voltage** | 10-32VDC |
| **EAN** | 5704438042674 |
| **IP rating** | IP68 |
| **Power draw (W)** | 2.6 |
| **UPC Code** | 879343042806 |
| **Connection** | 0.7m cable |
| **Current consumption (mA @ 12VDC)** | 150 |
| **Current consumption (mA @ 24VDC)** | 81 |
| **Min. feed wire gauge** | 0.5mm2 AWG22 |

| Specifications | |
|---|---|
| **Weight (Kg)** | 0.73 Kg |
| **Weight (Oz)** | 25.66 Oz |